



- NOTES:
1. RESISTANCE VALUES ARE SHOWN IN OHMS UNLESS OTHERWISE NOTED. (K-KILO OHM, M-MEG OHM)
  2. RESISTOR WATTAGES ARE 1/8W UNLESS OTHERWISE NOTED.
  3. CAPACITANCE VALUES ARE INDICATED IN MICRO FARADS UNLESS OTHERWISE NOTED. (P-MICRO-MICRO FARAD)
  4. CHIP PARTS ARE NOT SPECIFIED IN THIS SCHEMATIC DIAGRAM. PLEASE REFER TO THE PARTS LIST FOR THE CHIP PARTS.
  5. VOLTAGE IN  $\square$  SHOWS TX CONDITION.
  6. VOLTAGE IN  $\square$  SHOWS RX CONDITION UNDER OPERATION OF EACH FUNCTION.
  7. VOLTAGE IN NO MARK SHOWS RX CONDITION.

**DYNASCAN CORPORATION**  
**SCHEMATIC, 33 PLUS**

DESIGN BY 62.7.28	DRAWN BY TANA	UNIDEN NO. UT-320	MODEL NO. COBRA 33 PLUS
CHECK BY	APPROV BY	TITLE SCHEMATIC DIAGRAM	(1/5)
DRAWING NO. E12-2682 1/2			REV MARK

DATE: 2-8-88  
 PART NUMBER: 476006C1001