



NOTES:

1. All resistors are 5%, 1/4 watt, with value given in ohms, unless specified otherwise.
2. All capacitor values are given in uF, unless specified otherwise.
3. Symbols used:
 - chassis ground
 - p.c. board ground
 * indicates component value may vary from unit to unit

SEMICONDUCTOR	TERMINAL CONNECTION	(BOTTOM VIEW UNLESS OTHERWISE NOTED)
2SA 719	TOP VIEW	TOP VIEW
2SC 828	TOP VIEW	TOP VIEW
2SC 829	TOP VIEW	TOP VIEW
2SC 845	TOP VIEW	TOP VIEW
2SC 1318	TOP VIEW	TOP VIEW
2SC 1359	TOP VIEW	TOP VIEW
2SC 1047	TOP VIEW	TOP VIEW
2SC 1215	TOP VIEW	TOP VIEW
2SC 710	TOP VIEW	TOP VIEW
2SC 784	TOP VIEW	TOP VIEW
2SC 372	TOP VIEW	TOP VIEW
2SC 1687	TOP VIEW	TOP VIEW
2SC 1688	TOP VIEW	TOP VIEW
2SC 1306	TOP VIEW	TOP VIEW
2SC 1678	TOP VIEW	TOP VIEW
2SC 1816	TOP VIEW	TOP VIEW
2SD 313	TOP VIEW	TOP VIEW
2SC 1760	TOP VIEW	TOP VIEW
2SC 1957	TOP VIEW	TOP VIEW
TA7205P	TOP VIEW	TOP VIEW
BA 521	TOP VIEW	TOP VIEW

E : EMITTER
 C : COLLECTOR
 B : BASE

Figure 2-14. Schematic Diagram, Model 3084X